you can

Canon

Canon Desktop Laser Printer range
Multifunctional i-Sensys MF6560PL - MF9170
MF8180c (Colour) - Copy - Print - Scan - Fax

Canon Inc.
www.canon.com

Canon Europa NV
www.canon-europe.com

Canon UK Ltd
www.canon.co.uk

Canon (irl) Business Equipment Ltd
www.canon.ie

Find the perfect fit with **Careers@Canon**
www.canon-europe.com/about_us/careers/

For answers to your questions, details of repair centers and more, visit: www.support.canon-europe.com

WWF

Canon

Europe, Middle East & Africa
Conservation Partner

© 1986 Panda symbol WWF ® WWF Registered Trademark

CLUB
CLUB COPYING COMPANY LIMITED
020 7635-5252
Authorised Partner EST. 1981

We Speak Image

you can

Canon

Laser Printers & All-in-Ones range 2008

UEFA EURO2008 Austria-Switzerland

Official Sponsor of UEFA EURO 2008™

Set your business free

From simple home offices to busy SMEs, there's no better business partner than i-SENSYS.

Building a business requires tools you can rely on. Tools suited to the needs of your growing business. Canon engineers invented the first desktop laser printer in 1982. Since then, we have relentlessly pursued our goal of creating the perfect product that would combine productivity, efficiency and pure peace of mind. The result is the i-SENSYS range of laser office equipment.

The range extends from colour and monochrome printers to compact All-in-Ones that let you print, copy, scan and fax in a single convenient machine. The i-SENSYS MF4690PL can even scan directly to e-mail, to a network folder or to a USB memory device with SEND functionality.

All i-SENSYS printers produce smoother text, cleaner curves and subtler greys. Selected models print in brilliant full colour. With virtually no warm-up time, i-SENSYS responds immediately to every task. And straightforward networking integrates seamlessly into your existing setup.

Whatever the job – from reports and labels to envelopes and transparencies – there's an i-SENSYS laser up to the job. Let us handle the everyday tasks, so you have the freedom to focus on the big picture. Freedom to expand your business horizons. Freedom to grow.

FAST

Quick First Print gets you going faster. On-Demand Fixing Technology replaces conventional thermal rollers and has virtually zero warm-up time. i-SENSYS can even share the task of image processing between PC and printer.

EFFICIENT

SEND functionality facilitates paperless document transfer. Scan documents and distribute them automatically to multiple network destinations all in one simple operation.

CONNECTED
PCL support on selected models integrates i-SENSYS into your existing network environment, adding valuable resources for the entire workplace. With just one cable and a single software installation, setup could not be simpler.

EASY TO REPLACE
i-SENSYS combines toner, photosensitive drum, electrostatic charger and cleaning unit in an all-in-one cartridge that simply clicks into place. Our cartridge recycling programme reuses or recycles 100% of each unit.

TRUSTED
Canon's long tradition of innovation is why we are a market leader in the number of patents registered year after year. We research and develop our own cutting-edge technology, so our products are ideally suited to your business needs.

RELIABLE
The optional Canon Easy Service Plan lets you choose the level of service you require. Choose from next-day on-site service, return-to-base service, or for those who fancy convenience, we even offer a one-time installation service.

RESPONSIBLE
Our patented On-Demand Fixing means i-SENSYS has zero warm-up time, using up to 75% less power than standard technologies. Energy-efficient charging virtually eliminates ozone emissions in the workplace.

Living the sweet life

Growing up in Amsterdam, Loes Kamsteeg learned to love Italian cinema. Working as a film producer in Rome, she learned to love an i-SENSYS LBP5300.

"Two things are absolutely indispensable here: my Vespa and my i-SENSYS. Things can get pretty hectic. The Vespa gets me around quick and the i-SENSYS gives me quick, full-colour laser prints of all our location photos, with virtually no warm-up time."

"Black-and-white prints are even quicker. In this business, things are always changing. The script is all we have to keep everyone on the same page. Automatic double-sided printing makes me feel better about the amount of paper we go through."

Laser Beam Printers

i-SENSYS LBP5360

Designed for demanding workgroups, this compact, robust and quiet colour laser printer offers high specification performance. Network ready, PCL compatible and easy to use and maintain it delivers fast, professional output with automatic double-sided printing.

- Compact Colour Laser Printer: 21 ppm in colour & mono
- Automatic double-sided printing as standard
- PCL5c/6 & UFR II* supported for maximum compatibility
- Quick First Print performance; no warm-up time from sleep mode
- Fast 10 second first print time
- Network ready
- 128MB standard, expandable up to 384MB. Optional 20GB hard disk drive
- 9600 x 600 dpi – print resolution
- Colour All-in-One cartridges
- 250-sheet cassette, 100-sheet multi-purpose tray and optional 500-sheet cassette (max. A4)
- Windows, Mac** and Linux** compatible

* Canon's own printer language
** See specifications

i-SENSYS LBP5300

This quiet, network ready colour laser printer is designed for frequent, high-quality shared printing. The 21 ppm colour and mono output, large paper capacity, double-sided printing and maintenance-free colour All-in-One cartridges make it ideal for busy workgroups.

- Robust and compact Colour Laser Printer: 21 ppm in colour & mono
- Fast first colour print in approx. 10 seconds
- Maintenance free colour All-in-One cartridges containing S Toner for continuous professional quality
- 9600 x 600 dpi enhanced print resolution
- Zero warm-up time and quiet operation due to Colour On-Demand Fixing Technology
- Network ready with Remote User Interface (RUI)
- Automatic double-sided printing as standard
- Large paper capacity: 250-sheet cassette, 100-sheet multi-purpose tray and optional 500-sheet cassette (max. A4)
- USB2.0 Hi-Speed connection
- Windows, Mac* and Linux* compatible

* See specifications

i-SENSYS LBP5100

This compact colour laser printer delivers high quality output and impressive print speeds with quiet, easy operation. Built-in automatic duplexing allows the creation of more professional double-sided documents – while cutting down on paper costs.

- Compact and quiet Colour Laser Printer
- Impressive print speeds: 10 ppm in colour, 12 ppm in mono
- Built-in automatic double-sided printing
- 9600 x 600 dpi print resolution and S Toner for professional output with vivid, contrasting colours and sharp text
- Quick first print, zero warm-up time from sleep mode
- Fast first print out in approx. 20 seconds
- Colour All-in-One cartridges
- 250-sheet paper cassette plus optional 250-sheet cassette (max. A4)
- Small footprint with full frontal operation
- Network printing with optional NB-C2 Network card

i-SENSYS LBP5000

The i-sensys LBP5000 brings speed, simplicity and style to colour laser printing – with convenient, maintenance-free colour All-in-One cartridges. Benefit from fast, professional colour output at 8 ppm, with this smart, quiet and space-saving printer.

- Robust, smart and stylish desktop Colour Laser Printer
- Print speed: 8 ppm in colour & mono
- Maintenance-free with colour All-in-One cartridges
- Print quality: 600 x 600 dpi or 9600 x 600 dpi equivalent
- No warm-up time with Colour On-Demand Fixing Technology plus fast first colour print in under 20 seconds
- Paper capacity: 250 sheets plus optional 250-sheet cassette
- Space-saving design with full frontal operation
- Easy-to-use Windows graphical interface
- USB2.0 Hi-Speed connection between printer and PC
- Network printing with optional Canon Network Board NB-C2

i-SENSYS LBP3460

The compact i-sensys LBP3460 provides a complete out-of-the-box solution for professional quality laser printing. A fast 33 pages per minute print speed is combined with PCL5e/6 compatibility, built-in networking and duplexing and an extensive paper supply.

- 33 ppm heavy-duty Laser Printer
- PCL 5e/6 & UFR II* supported for maximum compatibility
- Built-in networking (TCP/IP) for sharing printer resources
- Built-in duplex unit to provide double sided printing
- No warm-up time and first print ready in 7.7 seconds or less
- Print quality: 600 x 600 dpi or 2400 x 600 dpi equivalent
- Maintenance-free All-in-One cartridge
- 250-sheet cassette and 100-sheet multi-purpose tray plus optional 500-sheet cassette
- USB2.0 Hi-Speed connection between printer and PC
- Stylish, space-saving design with full frontal operation

* Canon's own printer language

i-SENSYS LBP3370

Delivering the performance and productivity that dynamic workgroups demand, this rapid and robust desktop laser printer features a built-in network interface and fast double-sided printing. Handle workloads with ease whilst saving precious time and energy.

- 26 ppm mono printing
- Zero warm-up time from sleep mode
- Built-in networking (TCP/IP) for sharing printer resources
- First Print Out Time in only 6.5 seconds
- Built-in network interface with Remote User Interface (RUI)
- Printer Languages: PCL 5e/6 & UFR II*
- Save paper with automatic double-sided printing
- Max. 550-sheet paper capacity (250-sheet cassette, 50-sheet multi-purpose tray and optional 250-sheet cassette)
- Up to 2400 x 600 dpi print resolution
- Easy to use All-in-One cartridge: ensures continuous high quality output
- Compact, robust design
- Energy efficient – only 5 watts in sleep mode

* Canon's high performance printer language

i-SENSYS LBP3360

Share productive, professional output with this solid and compact network-ready Laser Printer. Easy to use and maintain, it has a 21 ppm print speed, practical PCL5e/6 & UFRII* support, cost-saving automatic double-sided printing and an All-in-One cartridge.

- 21 pages per minute Laser Printer
- PCL 5e/6 & UFRII* supported for maximum compatibility
- Network ready: built-in interface card
- Built-in duplex unit for double-sided printing
- Virtually no warm-up time, first print out time in less than 9 seconds
- 2400 x 600 dpi enhanced print resolution
- All-in-One cartridge for consistent high quality output & maintenance-free operation. High yield replacement cartridge available
- 250-sheet cassette + optional 250-sheet cassette (up to A4)
- Windows, Mac** & Linux** compatible; USB2.0 Hi-Speed
- Solid, stylish design with full frontal/top operation

* Canon's own printer language
** English only & web distribution only

i-SENSYS LBP3310

With this compact & high speed laser printer, busy offices benefit from instant, high quality prints. It leads the way with energy efficiency, paper handling capability and automatic double-sided printing.

- 26 ppm mono printing
- Zero warm up time from sleep mode
- First Print Out Time in only 6.5 seconds
- Save paper with automatic double-sided printing
- Max. 550-sheet paper capacity (250-sheet cassette, 50-sheet multi-purpose tray and optional 250-sheet cassette)
- CAPT – Canon Advanced Printing Technology
- Up to 2400 x 600 dpi print resolution
- Easy to use All-in-One cartridge: ensures continuous high quality output. Available in standard and high yield options
- Compact, robust design
- Optional network printing with NB-C2 Network Interface Card
- Energy efficient – only 4 watts in standby mode

i-SENSYS LBP3300

Benefit from a fast 21 pages per minute print speed and professional laser output with the i-sensys LBP3300. Productive features include standard double sided printing, a flexible paper supply and optional networking – in a space-saving and easy-to-use unit.

- High performance Laser Printer: 21 ppm
- Standard built-in duplex unit for double sided printing
- No warm-up time and first print ready in 9 seconds or less
- Print quality: 600 x 600 dpi or 2400 x 600 dpi equivalent
- Maintenance-free All-in-One cartridge
- Standard 250-sheet cassette plus optional 250-sheet cassette
- Superior processing speed due to CAPT* & SCoA**
- USB2.0 Hi-Speed connection between printer and PC
- Network printing with optional Canon Network Board NB-C2
- Stylish, space-saving design with full frontal operation

* CAPT = Canon Advanced Printing Technology
** SCoA = Smart Compression Architecture

i-SENSYS LBP3000

Get the print speed you need and the laser quality you expect, with the i-sensys LBP3000. Advanced Canon technologies ensure fast output, enhanced print quality and exceptional ease of use. Plus optional network printing makes it even more productive.

- Laser Printer with rapid print speed: 14 ppm
- No warm-up time or waiting with On-Demand Fixing Technology
- Fast first print out: under 9.3 seconds due to CAPT* & SCoA**
- All-in-One cartridge: easy to replace and ensures continuous high quality output
- High print quality: 600 x 600 dpi or 2400 x 600 dpi equivalent with Automatic Image Refinement
- Easy-to-use Windows graphical interface & 'sound assist' function
- Flexible paper handling and 150-sheet Multi Purpose Tray
- Optional network printing with AXIS 1650 Print Server
- Small, stylish and quiet in operation

* CAPT = Canon Advanced Printing Technology
** SCoA = Smart Compression Architecture

i-SENSYS LBP2900B
i-SENSYS LBP2900

Whether working at home or in a small office this compact and stylish laser printer meets all your needs and fits perfectly into your surrounding. Get fast, professional prints without waiting and benefit from quiet operation and energy saving efficiency.

- 12 ppm mono printing
- Compact and stylish design
- Zero warm-up time from sleep mode
- First Print Out Time in only 9.3 seconds
- Up to 2400 x 600 dpi print resolution
- CAPT - Canon Advanced Printing Technology
- Easy to use All-in-One cartridge: ensures continuous high quality output
- 150-sheet multi-purpose tray
- Optional network printing with AXIS 1650 Print Server
- Energy efficient – only 2 watts in sleep mode and quiet operation

Laser All-in-Ones

i-SENSYS MF8180C

The i-sensys MF8180C provides professional colour laser printing, copying, scanning and faxing in one compact, cost-cutting unit with built-in networking to add to productivity.
It's the ideal solution for all creative businesses where colour is critical.

- Desktop Colour Laser All-in-One: print, fax, copy, scan
- Printing at 2400 x 600 dpi (enhanced)
- 19 ppm/cpm in mono, 4 ppm/cpm in colour with no warm-up time and fast first print out
- Colour scanner: 9600 x 9600 dpi (enhanced)
- Super G3 faxing, 256-page* memory, Ultra High Quality imaging with 256 greyscales
- 50-page Automatic Document Feeder
- 250-sheet paper cassette, 125-sheet multi-purpose tray
- Standard built-in Ethernet interface for network printing/faxing
- Easy to replace toner and drum cartridges
- Simple installation and small footprint

* Based on ITU-T Standard Chart No. 1

i-SENSYS MF6580PL

The i-sensys MF6580PL provides fast and high performance laser printing, faxing, copying and colour scanning. The built-in network capability makes it ideal for sharing in small and mid-sized offices.

- Network ready Laser All-In-One: print, fax, copy, scan
- Printer languages: PCL5e, PCL6, Canon UFR-II LT
- 22 ppm/cpm, 1200 x 600 dpi print resolution (enhanced)
- Super G3 fax modem – 1280-page* fax memory and UHQ technology
- Colour scanner – 9600 x 9600 dpi (enhanced)
- 50-page Duplex Automatic Document Feeder & built-in duplex unit for double sided printing and copying
- 500-sheet paper cassette plus 100-sheet multi purpose tray
- All-in-One cartridge
- USB2.0 Hi-Speed interface

* Based on ITU-T Standard Chart No. 1

i-SENSYS MF6560PL
i-SENSYS MF6550

The i-sensys MF6560PL/MF6550 deliver high-speed and high-quality and provide the perfect solution for small and mid-sized businesses that need a complete print and communication centre.

- Laser All-In-One: print, fax, copy, scan
- Printer languages: PCL5e, PCL6 (MF6560PL), Canon UFR-II LT
- 22 ppm/cpm, 1200 x 600 dpi print resolution (enhanced)
- Super G3 fax modem – 1280-page* (MF6560PL)/256-page* (MF6550) fax memory and UHQ technology
- Colour scanner – 9600 x 9600 dpi (enhanced)
- 50-page Duplex Automatic Document Feeder & built-in duplex unit for double sided printing and copying
- 500-sheet paper cassette plus 100-sheet multi purpose tray
- All-in-One cartridge
- Optional network connectivity with AXIS 1650 Print Server

* Based on ITU-T Standard Chart No. 1

i-SENSYS MF6540PL
i-SENSYS MF6530

Benefit from fast, high quality laser printing, copying and colour scanning with the i-sensys MF6540PL and MF6530. Save time, space and money with these robust, yet stylish All-In-Ones, increasing productivity in small and mid-sized offices.

- Laser All-In-One: print, copy, scan
- Printer languages: PCL5e, PCL6 (MF6540PL), Canon UFR-II LT
- 22 ppm/cpm, 1200 x 600 dpi print resolution (enhanced)
- Colour scanner – 9600 x 9600 dpi (enhanced)
- 50-page Duplex Automatic Document Feeder & built-in duplex unit for double sided printing and copying
- 500-sheet paper cassette plus 100-sheet multi purpose tray
- All-in-One cartridge & USB2.0 Hi-Speed interface
- Robust, space-saving design
- Optional network connectivity with AXIS 1650 Print Server

i-SENSYS
MF4690PL

This compact and versatile laser All-in-One, with Super G3 fax, delivers high quality professional output. Maximum workgroup productivity is ensured with built-in networking, auto-duplexing, and SEND functionality to email, network and USB memory device.

- Compact laser All-in-One: printer, fax, copier & colour scanner
- Built-in automatic double-sided printing
- Built-in networking
- SEND functionality: scan documents direct to email, network, fax or a USB memory device
- PCL5e/6 & UFR II* support
- 128 MB memory as standard
- Super G3 fax modem with Department ID management security, a 256-page** fax memory & UHQ 256 greyscales
- Virtually no warm-up time: first copy in 8.5 seconds
- 20 ppm/cpm, 1200 x 600 dpi print resolution
- 35-sheet ADF
- All-in-One Cartridge
- Windows & Mac*** compatible

* Canon's own printer language
** Based on ITU-T Standard Chart No. 1
*** See specifications

i-SENSYS
MF4660PL

This high quality, laser All-in-One with built-in networking offers print, copy and colour scan functionality in a compact and stylish unit. Cut paper costs and produce more professional documents and booklets with built-in automatic double-sided printing.

- Compact and stylish laser All-in-One: printer, copier and colour scanner
- Built-in automatic double-sided printing
- Built-in networking
- PCL5e/6 & UFR II* support for maximum compatibility
- Department ID management security to control copying costs
- 128MB memory as standard
- Virtually no warm-up time: first copy in 8.5 seconds
- 20 ppm/cpm, 1200 x 600 dpi print resolution
- 35-sheet ADF
- Colour scanner: 9600 x 9600 dpi enhanced, save to PDF functionality
- All-in-One Cartridge
- Windows & Mac** compatible

* Canon's own printer language
** See specifications

i-SENSYS MF4270

Small, busy offices will find this compact, complete and stylish network-ready communication centre the ideal solution. It offers fast, professional laser printing, faxing, copying and colour scanning – with cost-cutting auto duplexing and energy efficiency.

- All-in-One: print, fax, copy and colour scan functionality
- 20 ppm monochrome printing and copying
- Built-in network interface with Remote User Interface (RUI)
- Super G3 fax modem – 3 seconds per page* transmission
- Virtually zero warm-up time from sleep mode
- No waiting: First Copy Out Time in 8.6 seconds
- Save paper with Automatic double-sided printing
- Up to 1200 x 600 dpi print resolution
- Colour scanning: up to 9600 x 9600 dpi
- 32 MB shared memory
- 35-sheet Automatic Document feeder and 250-sheet paper tray (max. A4)
- Easy to use All-in-One Cartridge, ensures continuous high quality output
- Energy efficient – only 3 watts in sleep mode

* Based on ITU-T Standard chart N.1
** See specifications

i-SENSYS MF4150

This compact Laser All-in-One provides high quality printing, faxing, copying and colour scanning – with a 35-sheet Automatic Document Feeder and automatic double-sided printing. Easy to use and maintain, it offers optional networking for shared productivity.

- Compact and stylish Laser All-in-One: printer, fax, copier and colour scanner
- Virtually no warm-up time – First copy output time in less than 10 seconds
- 20 ppm/cpm, 1200 x 600 dpi printing (enhanced)
- Super G3 fax modem, 256-page* fax memory, UHQ 256 greyscales
- Colour scanner: 9600 x 9600 dpi enhanced, save to PDF functionality
- Productive 35-sheet Automatic Document Feeder and 250- sheet paper cassette (max. A4)
- Automatic double-sided printing as standard
- All-in-One Cartridge: continuous high quality and maintenance-free operation
- Windows & Mac compatible;** USB2.0 Hi-Speed

* Based on ITU-T Standard Chart No. 1
** See specifications

i-SENSYS MF4140

Make quick, high quality laser prints and copies, fax perfectly and scan in colour. Handle everything easily with this compact laser All-in-One. Save time and cut paper costs with automatic double-side printing. Optional networking adds to productivity.

- Laser All-in-One: printer, fax, copier and colour scanner
- Virtually no warm-up time – First copy output time in less than 10 seconds
- 20 ppm/cpm, 1200 x 600 dpi printing (enhanced)
- Super G3 fax modem, 3 seconds per page* transmission 256-page* fax memory, UHQ technology with 256 greyscales
- Colour scanner: 9600 x 9600 dpi enhanced, save to PDF functionality
- Automatic double-sided printing as standard
- 250-sheet paper cassette (max. A4)
- All-in-One Cartridge: continuous high quality and maintenance- free operation
- Windows & Mac compatible;** USB2.0 Hi-Speed
- Compact, stylish design

* Based on ITU-T Standard Chart No. 1
** See specifications

i-SENSYS MF4120

Take advantage of quick, high quality laser printing, copying and colour scanning that is affordable and easy to use. This compact All-in-One features automatic double-sided printing to cut paper costs and save time. Optional networking enhances productivity.

- Affordable Laser All-in-One: printer, copier and colour scanner
- Virtually no warm-up time – first copy output time in less than 10 seconds
- 20 prints/copies per minute
- 1200 x 600 dpi printing (enhanced)
- Colour scanner: 9600 x 9600 dpi enhanced, save to PDF functionality
- Automatic double-sided printing as standard
- 250-sheet paper cassette (max. A4)
- All-in-One Cartridge: continuous high quality and maintenance free operation
- Windows & Mac compatible;* USB2.0 Hi-Speed
- Stylish and compact with small footprint

* See specifications

i-SENSYS MF4010

Affordable, compact and easy to use, this complete print, copy and colour scan solution is ideal for small and home office use. Quick First-Print and high quality output ensure maximum productivity.

- Affordable laser All-in-One: mono printer, copier and colour scanner
- Virtually no warm-up time – first copy output time in less than 9 seconds
- Quick First-Print performance
- 20 prints/copies per minute
- 1200 x 600 dpi printing (enhanced) and high quality copying
- 9600 x 9600 dpi scanning (enhanced), with save to PDF functionality
- 32 MB shared memory
- All-in-One Cartridge FX-10, continuous high quality and virtually maintenance-free operation
- Stylish and compact with small footprint
- 250-sheet paper tray (max. A4)
- Network printing/scanning with optional AXIS 1650 Print Server

Symbol Guide

Automatic Image Refinement makes tight curves smooth and beautiful by delivering the equivalent of 2400 x 600 dpi – with no impact on print speed.

Canon Recyclable Cartridges. Since 1990, Canon has a worldwide cartridge recycling program. Canon's toner cartridge recycling program is a zero landfill program in which every component of a used toner cartridge is reused or recycled, saving precious natural resources. See more on www.canon-europe.com/recycling

Canon Advanced Printing Technology (CAPT / COLOR CAPT) is a combination of hardware and software that optimizes print data processing for faster print speed.

Energy Star indicates Canon products meet Energy Star requirements.

High-capacity toner cartridges reduce your cost per copy.

Canon's on demand fixing technology springs to action when required, for almost no waiting and no negligible energy use.

SUPER G3: the longer the transmission time, the more costs you incur. Super G3 faxes boast the fastest analogue transmission speed available (33.6 Kbps) – one A4 page every 3 seconds.

UHQ ensures exceptional image quality when sending fine text, diagrams and photos. 256 greyscale reproductions produce perfect halftones on faxes and copiers.

Certified USB and Certified Hi-Speed USB connectivity provides a fast, easy connection between product and computer.

Authentic Canon Laser Cartridges give you reliable high quality prints.

Laser Accessories Chart

OPTIONAL PAPER CASSETTES / FEEDERS	PAPER FEEDER PF-35	PAPER FEEDER PF-35P	PAPER FEEDER PF-36	PAPER FEEDER PF-92	PAPER FEEDER PF-93	CASSETTE UNIT M1	OPTIONAL NETWORKBOARDS	NETWORK CARD NB-C2	HARDDISK HD-93	NETWORK PRINTSERVER AXIS 1650 EU	NETWORK PRINTSERVER AXIS 1650 GB	OPTIONAL TELEPHONE HANDSET	TELEPHONE HANDSET TEL 6 KIT	TELEPHONE HANDSET 6 KIT (LONG CORD-CW)	TELEPHONE HANDSET 6 BLACK KIT (LONG CORD-CW)	FAX HANDSET REST FP*	OTHER OPTIONS	EXPANSION RAM ER-64	EXPANSION RAM ER-128	EXPANSION RAM ER-256
LASER PRINTERS																				
i-SENSYS LBP5360					●				●										●	●
i-SENSYS LBP5300					●															
i-SENSYS LBP5100				●				●												
i-SENSYS LBP5000				●				●												
i-SENSYS LBP3460			●															●	●	●
i-SENSYS LBP3370		●																		
i-SENSYS LBP3360		●																		
i-SENSYS LBP3310		●						●												
i-SENSYS LBP3300	●							●												
i-SENSYS LBP3000										●	●									
i-SENSYS LBP2900/LBP2900B										●	●									
LASER ALL-IN-ONES																				
i-SENSYS MF8180C																				
i-SENSYS MF6580PL						●							●			●				
i-SENSYS MF6560PL/MF6550						●				●	●		●			●				
i-SENSYS MF6540PL/MF6530						●				●	●									
i-SENSYS MF4690PL														●						
i-SENSYS MF4660PL																				
i-SENSYS MF4270															●					
i-SENSYS MF4150										●	●			●						
i-SENSYS MF4140										●	●			●						
i-SENSYS MF4120										●	●									
i-SENSYS MF4010										●	●									

* only in combination with Telephone handset

Cartridges and toner

Canon
Recycling used cartridges

Authentic
LASER CARTRIDGES
FOR i-SENSYS

Choose quality. Choose *Authentic Canon Laser Cartridges.*

Life is full of compromises. Be sure to choose a replacement cartridge that won't let you down. Only *Authentic Canon Laser Cartridges* are engineered with a perfect understanding of the advanced i-SENSYS system – to ensure superior quality results print after print.

Canon's pioneering All-in-One cartridges simply snap into place for easy, non-stop printing. Inside, Canon EF Toner and S Toner create smudge- and shine-free copies that you can write on immediately.

All our cartridges are designed to minimise or even eliminate detrimental impact on the environment, while still ensuring the high output and high quality today's businesses demand. Canon's global cartridge recycling programme reuses or recycles every component. Since 1990, we've collected and processed more than 190,000 tonnes of used cartridges, reducing both waste and CO_2 emissions.

www.canon.co.uk/recycling

All-in-One cartridge

Canon's All-in-One cartridge contains all of your printer's essential parts, so replacing the toner also performs a free printer maintenance. No mess, no hassle – just continuous high quality output every time. To help protect the environment, all cartridge elements are completely recyclable.

Cartridges Compatibility Chart

All-in-One Laser Cartridge	Cartridge 701 B 9287A003 Yield: 5,000*	Cartridge 701 Y 9284A003 Cartridge 701 M 9285A003 Cartridge 701 C 9286A003 Yield: 4, 000*	Cartridge 701 L Y 9288A003 Cartridge 701 L M 9289A003 Cartridge 701 L C 9290A003 Yield: 2,000*	Cartridge 701 Drum 9623A003 Yield: 5,000* (C)/20,000 (Y)	Cartridge 703 7616A005 Yield: 2,000**	Cartridge 706 0264B002 Yield: 5,000**	Cartridge 707 B 9424A004 Yield: 2,500*	Cartridge 707 Y 9421A004 Cartridge 707 M 9422A004 Cartridge 707 C 9423A004 Yield: 2,000*	Cartridge 708 0266B002 Yield: 2,500**	Cartridge 708H 0917B002 Yield: 6,000**	Cartridge 710 0985B001 Yield: 6,000**	Cartridge 710H 0986B001 Yield: 12,000**	Cartridge 711B 1660B002 Cartridge 711Y 1657B002 Cartridge 711M 1658B002 Cartridge 711C 1659B002 Yield: 6.000*	Cartridge 715 1975B002 Yield: 3,000**	Cartridge 715H 1976B002 Yield: 7,000**	FX-10 0263B002 Yield: 2,000*
LASER PRINTERS																
i-SENSYS LBP5360													●			
i-SENSYS LBP5300													●			
i-SENSYS LBP5100							●	●								
i-SENSYS LBP5000							●	●								
i-SENSYS LBP3460											●	●				
i-SENSYS LBP3370														●	●	
i-SENSYS LBP3360									●	●						
i-SENSYS LBP3310														●	●	
i-SENSYS LBP3300									●	●						
i-SENSYS LBP3000					●											
i-SENSYS LBP2900/LBP2900B					●											
LASER ALL-IN-ONES																
i-SENSYS MF8180C	●	●	●	●												
i-SENSYS MF6580PL						●										
i-SENSYS MF6560PL/MF6540PL						●										
i-SENSYS MF6550/MF6530						●										
i-SENSYS MF4690PL																●
i-SENSYS MF4660PL																●
i-SENSYS MF4270																●
i-SENSYS MF4150																●
i-SENSYS MF4140																●
i-SENSYS MF4120																●
i-SENSYS MF4010																●

* A4, at 5% coverage
** A4, based on ISO/IEC19752

Laser Printers Specifications

		i-SENSYS LBP5360	i-SENSYS LBP5300	i-SENSYS LBP5100	i-SENSYS LBP5000
PRINTING METHOD AND QUALITY					
Printing Method		Colour Laser beam printing with built-in duplex unit	Colour Laser beam printing with built-in duplex unit	Colour Laser beam printing	Colour Laser beam printing
Printer Language		PCL5c/PCL6 and UFRII	CAPT (Canon Advanced Printing Technology)	CAPT (Canon Advanced Printing Technology)	CAPT (Canon Advanced Printing Technology)
Resolution		600 x 600 dpi (Max. 9600 x 600 dpi with AIR)	600 x 600 dpi (Max. 9600 x 600 dpi with AIR)	600 x 600 dpi (Max. 9600 x 600 dpi with AIR)	600 x 600 dpi (Max. 9600 x 600 dpi with AIR)
PRINT SPEED					
Mono Text		Mono: 21 ppm A4 Colour: 21 ppm A4	Mono: 21 ppm A4 Colour: 21 ppm A4	Mono: 12 ppm A4 Colour: 10 ppm A4	Mono: 8 ppm A4 Colour: 8 ppm A4
Duty Cycle		Up to 60,000 pages per month	Up to 55,000 pages per month	Up to 35,000 pages per month	Note[1]
MEDIA HANDLING AND SUPPORT					
Paper Size		A4, B5, A5, Legal, Letter, Executive, Statement, 8.5 x 13, 16K, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 – 215.9mm, length 127.0 – 355.6mm)	A4, B5, A5, Legal, Letter, Executive, Statement, 8.5 x 13, 16K, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 – 215.9mm, length 127.0 – 355.6mm)	A4, B5, A5, Legal, Letter, Executive, Statement, 8.5 x 13, 16K, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 – 215.9mm, length 127.0 – 355.6mm)	A4, B5, A5, Legal, Letter, Executive, Statement, 8.5 x 13, 16K, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 – 215.9mm, length 127.0 – 355.6mm)
Media Weight		64 – 220g/m^2	64 – 220 g/m^2	64 – 163g/m^2	64 – 163g/m^2
Media Handling		250 sheet paper cassette/ 100 sheets Multipurpose tray (+500 sheet optional cassette)	250 sheet paper cassette/ 100 sheets Multipurpose tray (+500 sheet optional cassette)	250 sheet paper cassette/single sheet Multipurpose slot (+250 sheet optional cassette)	250 sheet paper cassette/single sheet Multipurpose slot (+250 sheet optional cassette)
Paper Output		200 sheets	200 sheets	125 sheets face-down	125 sheets face-down
Memory		128MB SDRAM Standard (expandable up to 384MB)	16MB with CAPT & Hi-SCoA technology	16MB with CAPT & Hi-SCoA technology	8MB with CAPT & Hi-SCoA technology
TONER CARTRIDGE INFORMATION					
Toner Cartridge Life		Cartridge 711 Blk: 6,000 pages Cartridge 711 C/M/Y: 6,000 pages (A4, at 5% coverage)	Cartridge 711 Blk: 6,000 pages Cartridge 711 C/M/Y: 6,000 pages (A4, at 5% coverage)	Cartridge 707 Blk: 2,500 pages (A4, at 5% coverage) Cartridge 707 C/M/Y: 2,000 pages (A4, at 5% coverage)	Cartridge 707 Blk: 2,500 pages Cartridge 707 C/M/Y: 2,000 pages (A4, at 5% coverage)
DEVICE CHARACTERISTICS					
Interface		Standard: USB 2.0 Hi-Speed, IEEE1284, 10Base-T/100Base-TX	Standard: USB 2.0 Hi-Speed, 10Base-T/100Base-TX	Standard: USB 2.0 Hi-Speed, Optional: 10Base-T/100Base-TX	Standard: USB 2.0 Hi-Speed, Optional: 10Base-T/100Base-TX
Dimensions (W x D x H)		412 x 453 x 470.7mm	412 x 453 x 470.7mm	407 x 365 x 395mm	407 x 365 x 374mm
Weight		Approx. 22kg (without cartridge)	Approx. 22kg (without cartridge)	Approx. 18kg (without cartridge)	Approx. 16kg (without cartridge)
POWER					
Consumption	**Sleep**	Approx. 15W	Approx. 13W	Approx. 8W	Approx. 11W
	Standby	Approx. 45W	Approx. 45W	Approx. 16W	Approx. 18W
	Operation	Approx. 416W	Approx. 415W	Approx. 340W	Approx. 207W
Acoustic Noise Levels		Max. 53dB(A) or less (during operation) 35dB(A) or less (during standby)	Max. 53dB(A) or less (during operation)	Max. 50dB(A) or less (during operation) 25dB(A) or less (during standby)	Max. 50dB(A) or less (during operation) 25dB(A) or less (during standby)
OPERATING ENVIRONMENT					
Temperature Range		10 – 30°C	10 – 30°C	10 – 30°C	10 – 30°C
Humidity		10 – 80% RH	10 – 80% RH	10 – 80% RH	10 – 80% RH
OPERATING SYSTEM REQUIREMENTS					
Operating Systems		Windows® 98/SE/ME/2000/XP/ Vista/Server 2003/Mac OS X v10.3.x, v10.4.x, v10.5.x (English driver only and online distribution only)/ Linux (English driver only and online distribution only)/With Server-Based Computing Environment. Compatible Windows Terminal Server (Service): Microsoft Windows 2000 Server, Server 2003. Compatible Software: Citrix MetaFrame 1.8, Presentation server 3.0 and 4.0 Compatible Microsoft Cluster Server (MSCS): Microsoft Windows 2000 Advanced Server, Server 2003 Enterprise Edition	Windows® 98/ME/2000/ XP/Vista (32 bit only)/Server 2003/Mac OS X v10.3.x, v10.4.x, v10.5.x (English driver only and online distribution only)/ Linux (English driver only and online distribution only)	Windows® 98/ME/2000/ XP/Vista (32 bit only)/Server 2003/Mac OS X v10.3.x, v10.4.x, v10.5.x (English driver only and online distribution only)/ Linux (English driver only and online distribution only)	Windows® 98/ME/2000/ XP/Vista (32 bit only)/Server 2003/Mac OS X v10.3.x, v10.4.x, v10.5.x (English driver only and online distribution only)/ Linux (English driver only and online distribution only)

Standard disclaimer

[a] All specifications subject to change without notice

Footnotes

[1] Specification not available at time of print

Laser Printers Specifications

		i-SENSYS LBP3460	i-SENSYS LBP3370	i-SENSYS LBP3360	i-SENSYS LBP3310
PRINTING METHOD AND QUALITY					
Printing Method		Monochrome Laser beam printing	Monochrome Laser beam printing	Monochrome Laser beam printing	Monochrome Laser beam printing
Printer Language		PCL5e/PCL6 and UFRII	PCL5e/PCL6 and UFRII	PCL5e/PCL6 and UFRII	CAPT (Canon Advanced Printing Technology)
Resolution		600 x 600 dpi (Max. 2400 x 600 dpi with AIR)	600 x 600 dpi (Max. 2400 x 600 dpi with AIR)	600 x 600 dpi (Max. 2400 x 600 dpi with AIR)	600 x 600 dpi (Max. 2400 x 600 dpi with AIR)
PRINT SPEED					
Mono Text		33 ppm A4	26 ppm A4	21 ppm A4	26 ppm A4
Duty Cycle		Up to 90,000 pages per month	Up to 15,000 pages per month	Up to 10,000 pages per month	Up to 10,000 pages per month
MEDIA HANDLING AND SUPPORT					
Paper Size		A4, B5, A5, Legal, Letter, Executive, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 – 215.9mm, length 127.0 – 355.6mm)	A4, B5, A5, Legal, Letter, Executive, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 – 215.9mm, length 127.0 – 355.6mm)	A4, B5, A5, Legal, Letter, Executive, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 – 215.9mm, length 127.0 – 355.6mm)	A4, B5, A5, Legal, Letter, Executive, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 – 215.9mm, length 127.0 – 355.6mm)
Media Weight		64 – 199 g/m^2	64 – 163 g/m^2	64 – 163 g/m^2	64 – 163 g/m^2
Media Handling		250 sheet paper cassette, 100 sheets Multipurpose tray, 500-sheet optional cassette	250 sheet paper cassette, 50 sheets Multipurpose tray, 250-sheet optional cassette	250 sheet paper cassette, single sheet Multipurpose slot, 250-sheet optional cassette	250 sheet paper cassette, 50 sheets Multipurpose tray, 250-sheet optional cassette
Paper Output		250 sheets (face-down), 50 sheets (face-up)	125 sheets (face-down), 1 sheet (face-up)	125 sheets (face-down), 1 sheet (face-up)	125 sheets (face-down), 1 sheet (face-up)
Memory		64MB SDRAM, Expandable up to 320MB	64MB	64MB	8MB with CAPT & Hi-SCoA technology
TONER CARTRIDGE INFORMATION					
Toner Cartridge Life		Cartridge 710: 6,000 pages Cartridge 710H: 12,000 pages (A4, based on ISO/IEC19752)	Cartridge 715: 3,000 pages Cartridge 715H: 7,000 pages (A4, based on ISO/IEC19752)	Cartridge 708: 2,500 pages Cartridge 708H: 6,000 pages (A4, based on ISO/IEC19752)	Cartridge 715: 3,000 pages Cartridge 715H: 7,000 pages (A4, based on ISO/IEC19752)
DEVICE CHARACTERISTICS					
Interface		Standard: USB 2.0 Hi-Speed, 10Base-T/100Base-TX	Standard: USB 2.0 Hi-Speed, 10Base-T/100Base-TX	Standard: USB 2.0 Hi-Speed, 10Base-T/100Base-TX	Standard: USB 2.0 Hi-Speed, Optional 10/100Base-TX
Dimensions (W x D x H)		445 x 410 x 273mm	399.7 x 378.6 x 267mm	399.7 x 375.7 x 267mm	399.7 x 378.6 x 258mm
Weight		Approx. 16.1kg (without cartridge)	Approx. 11.4kg (without cartridge)	Approx. 12kg (without cartridge)	Approx. 11.2kg (without cartridge)
POWER					
Consumption	**Standby**	Approx. 11W (6W in sleep mode)	Approx. 9W (5W in sleep mode)	Approx. 11W (4W in sleep mode)	Approx. 4W
	Printing	Approx. 572W	Approx. 403W	Approx. 400W	Approx. 392W
Acoustic Noise Levels		Max. 52dB(A) or less (during operation) Background noise only (during standby)	Max. 55dB(A) or less (during operation) Background noise only (during standby)	Max. 50.9dB(A) or less (during operation) Background noise only (during standby)	Max. 55dB(A) or less (during operation) Background noise only (during standby)
OPERATING ENVIRONMENT					
Temperature Range		10 – 30°C	10 – 30°C	10 – 30°C	10 – 30°C
Humidity		10 – 80% RH	20 – 80% RH	20 – 80% RH	20 – 80% RH
OPERATING SYSTEM REQUIREMENTS					
Operating Systems		Windows® 98/ME/2000/XP/Server 2003/Vista/Mac OS X Version 10.2.x, 10.3.x, 10.4.x, 10.5.x (Online distribution only)/Linux (English driver and online distribution only)/ With Server-Based Computing Environment. Compatible Windows Terminal Server (Service): Microsoft Windows 2000 Server, Server 2003. Compatible Software: Citrix MetaFrame 1.8, Presentation server 3.0 and 4.0 Compatible Microsoft Cluster Server (MSCS): Microsoft Windows 2000 Advanced Server, Server 2003 Enterprise Edition/ Netware option	Windows® 2000/XP/Server 2003/Vista/ Mac OS X Version 10.2.x, 10.3.x, 10.4.x, 10.5.x (Online distribution only)/ Linux (English driver and online distribution only)/With Server-Based Computing Environment. Compatible Windows Terminal Server (Service): Microsoft Windows 2000 Server, Server 2003. Compatible Software: Citrix MetaFrame 1.8, Presentation server 3.0 and 4.0 Compatible Microsoft Cluster Server (MSCS): Microsoft Windows 2000 Advanced Server, Server 2003 Enterprise Edition	Windows® 98/ME/2000/XP/Server 2003/Vista/Mac OS X Version 10.2.x, 10.3.x, 10.4.x,10.5.x (Online distribution only)/Linux (English driver and online distribution only)/With Server-Based Computing Environment. Compatible Windows Terminal Server (Service): Microsoft Windows 2000 Server, Server 2003. Compatible Software: Citrix MetaFrame 1.8, Presentation server 3.0 and 4.0 Compatible Microsoft Cluster Server (MSCS): Microsoft Windows 2000 Advanced Server, Server 2003 Enterprise Edition	Windows® 2000/XP/Server 2003/Vista/ Mac OS X Version 10.2.x, 10.3.x, 10.4.x, 10.5.x (Online distribution only)/ Linux (English driver and online distribution only)

Standard disclaimer

[a] All specifications subject to change without notice

Footnotes

[1] Specification not available at time of print

Laser Printers Specifications

		i-SENSYS LBP3300	i-SENSYS LBP3000	i-SENSYS LBP2900B	i-SENSYS LBP2900
PRINTING METHOD AND QUALITY					
Printing Method		Monochrome Laser beam printing	Monochrome Laser beam printing	Monochrome Laser beam printing	Monochrome Laser beam printing
Printer Language		CAPT (Canon Advanced Printing Technology)	CAPT (Canon Advanced Printing Technology)	CAPT (Canon Advanced Printing Technology)	CAPT (Canon Advanced Printing Technology)
Resolution		600 x 600 dpi (Max. 2400 x 600 dpi with AIR)	600 x 600 dpi (Max. 2400 x 600 dpi with AIR)	600 x 600 dpi (Max. 2400 x 600 dpi with AIR)	600 x 600 dpi (Max. 2400 x 600 dpi with AIR)
PRINT SPEED					
Mono Text		21 ppm A4	14 ppm A4	12 ppm A4	12 ppm A4
Duty Cycle		Up to 8,000 pages per month	Up to 5,000 pages per month	Note[1]	Note[1]
MEDIA HANDLING AND SUPPORT					
Paper Size		A4, B5, A5, Legal, Letter, Executive, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 – 215.9mm, length 127.0 – 355.6mm)	A4, B5, A5, Legal, Letter, Executive, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 – 215.9mm, length 127.0 – 355.6mm)	A4, B5, A5, Legal, Letter, Executive, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 – 215.9mm, length 127.0 – 355.6mm)	A4, B5, A5, Legal, Letter, Executive, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 – 215.9mm, length 127.0 – 355.6mm)
Media Weight		64 – 163 g/m^2	64 – 163 g/m^2	64 – 163 g/m^2	64 – 163 g/m^2
Media Handling		250 sheet paper cassette, single sheet Multi-purpose slot, 250-sheet optional cassette	Multipurpose tray: approx. 150 sheets	Multipurpose tray: approx. 150 sheets	Multipurpose tray: approx. 150 sheets
Paper Output		125 sheets (face-down), 1 sheet (face-up)	100 sheets (face-down)	100 sheets (face-down)	100 sheets (face-down)
Duplex Print		Automatic (Standard)	No	No	No
Memory		8MB with CAPT & Hi-SCoA technology	2MB with CAPT & SCoA technology	2MB with CAPT & SCoA technology	2MB with CAPT & SCoA technology
TONER CARTRIDGE INFORMATION					
Toner Cartridge Life		Cartridge 708: 2,500 pages Cartridge 708H: 6,000 pages (A4, based on ISO/IEC19752)	Cartridge 703: 2,000 pages (A4, based on ISO/IEC19752)	Cartridge 703: 2,000 pages (A4, based on ISO/IEC19752)	Cartridge 703: 2,000 pages (A4, based on ISO/IEC19752)
DEVICE CHARACTERISTICS					
Interface		Standard: USB 2.0 Hi-Speed, Optional 10/100Base-TX	Standard: USB 2.0 Hi-Speed	Standard: USB 2.0 Hi-Speed	Standard: USB 2.0 Hi-Speed
Dimensions (W x D x H)		369.7 x 375.7 x 257.7mm	370 x 251 x 217mm	370 x 251 x 217mm	370 x 251 x 217mm
Weight		Approx. 11kg (without cartridge)	Approx. 5.7kg (without cartridge)	Approx. 5.7kg (without cartridge)	Approx. 5.7kg (without cartridge)
POWER					
Consumption	**Standby**	Approx. 4W	Approx. 2W	Approx. 2W	Approx. 2W
	Printing	Approx. 436W	Approx. 259W	Approx. 259W	Approx. 259W
Acoustic Noise Levels		Max. 52.8dB(A) or less (during operation) 25dB(A)(during standby)	Max. 48dB(A) or less (during operation) Background noise only (during standby)	Max. 48dB(A) or less (during operation) Background noise only (during standby)	Max. 48dB(A) or less (during operation) Background noise only (during standby)
OPERATING ENVIRONMENT					
Temperature Range		10 – 32ºC	10 – 32.5ºC	10 – 32.5ºC	10 – 32.5ºC
Humidity		20 – 80% RH	20 – 80% RH	20 – 80% RH	20 – 80% RH
OPERATING SYSTEM REQUIREMENTS					
Operating Systems		Windows® 98/ME/2000/XP/Server 2003/ Vista (32bit only)/Linux (English driver and online distribution only)	Windows® 98/ME/2000/XP/ Server 2003/Vista (32bit only)/ Linux (English driver and online distribution only)	Windows® 98/ME/2000/XP/ Server 2003/ Vista (32bit only)/ Linux (English driver and online distribution only)	Windows® 98/ME/2000/XP/ Server 2003/ Vista(32bit only)/ Linux (English driver and online distribution only)

Standard disclaimer

[a] All specifications subject to change without notice

Footnotes

[1] Specification not available at time of print

Laser All-In-Ones Specifications

	i-SENSYS MF8180C	i-SENSYS MF6580PL	i-SENSYS MF6560PL/MF6540PL
TYPE			
Machine Type	Colour laser Flatbed All-in-One	Laser Flatbed All-in-One	Laser Flatbed All-in-One
Available Functions	Colour Print, Colour Scan, Colour Copy, Fax	Print, Fax, Copy, Colour Scan	Fax (MF6560PL only), Print, Copy, Colour Scan
Paper Scanning Type	Flatbed and Automatic Document Feeder	Flatbed and Automatic Document Feeder	Flatbed and Automatic Document Feeder
PRINTER FUNCTIONS			
Printing Method	Colour Laser beam printing	Monochrome Laser beam printing	Monochrome Laser beam printing
Printer Language	CARPS (Canon Advanced Raster Printing System)	PCL5e/ PCL6, Canon UFR-II LT	PCL5e/ PCL6, Canon UFR-II LT
Print Speed	19 ppm mono / 4 ppm colour	22 ppm	22 ppm
Duty Cycle	Up to 30,000 pages per month	Up to 15,000 pages per month	Up to 15,000 pages per month
Print Resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
Printer Memory	128MB (Shared)	128MB (shared)	128MB (shared)
Cartridges	Toner cartridge 701 Blk/C/M/Y, Drum cartridge	Cartridge 706	Cartridge 706
Yield	Cartridge 701 BLK 5,000 pages at 5% coverage, Cartridge 701L Cyan/Mag/Yel – 2,000 pages at 5% coverage (Included with machine) Cartridge 701 Cyan/Mag/Yel – 4,000 pages at 5% coverage/ Drum cartridge 701 – 20000 pages mono / 5000 pages colour	5,000 pages (based on ISO/IEC19752)	5,000 pages (based on ISO/IEC19752)
Smoothing	2400 x 600 dpi	1200 x 600 dpi	1200 x 600 dpi
Paper Capacity	250 sheet cassette + 125 sheets Multipurpose tray	500 sheet cassette +100 sheets Multipurpose tray (+500 sheet optional cassette)	500 sheet cassette + 100 sheets Multipurpose tray (+500 sheet optional cassette)
Paper Size	A4, A5, B5, LTR, LGL, EXE, ENVELOPE, Index Cards	A4, LTR, LGL, Envelope (COM10, Monarch, DL, ISO-5)	A4, A5, B5, LTR, LGL, EXE, ENVELOPE, Index Cards
Printing Width	216mm	216mm	216mm
Duplex Print	No	Automatic (Standard)	Automatic (Standard)
Toner Saver Mode	YES (for mono printing only)	YES	YES
FAX FUNCTIONS			
Stand-alone Fax	YES	YES	YES (MF6560PL)
PC Fax	YES (TX only)	YES (TX only)	YES (TX only) (MF6560PL)
Transmission Speed	Approx. 3 seconds per page (based on ITU-T Chart No.1)	Approx. 3 seconds per page (based on ITU-T Chart No.1)	Approx. 3 seconds per page (based on ITU-T Chart No.1) (MF6560PL)
Modem Speed	Super G3, 33.6Kbps	Super G3, 33.6Kbps	Super G3, 33.6Kbps (MF6560PL)
Compression Method	MH, MR, MMR, JBIG	MH, MR, MMR, JBIG	MH, MR, MMR, JBIG (MF6560PL)
Fax Resolution	Standard, Fine, Super Fine, Ultra Fine	Standard, Fine, Super Fine, Ultra Fine	Standard, Fine, Super Fine, Ultra Fine (MF6560PL)
Image Processing System	UHQ	UHQ	UHQ (MF6560PL)
Half-tone	256 grey scale	256 grey scale	256 grey scale (MF6560PL)
Automatic Document Feeder	50 pages	50 pages (Duplex)	50 pages (Duplex) (MF6560PL)
Memory Transmission	YES	YES	YES (MF6560PL)
Fax Memory	256 pages	1,280 pages as max.	1,280 pages (MF6560PL)
Memory Back-up	YES (1 hour)	YES (1 hour)	YES (1 hour) (MF6560PL)
Dual Access	YES	YES	YES (MF6560PL)
One-touch Dials/Coded Dials	18/100	23/100	23/100 (MF6560PL)
Group Dial	117	122	122 (MF6560PL)
Redial	YES	YES	YES (MF6560PL)
Answering Machine Hook-up	YES	YES	YES (MF6560PL)
Remote Reception	YES	YES	YES (MF6560PL)
Sequential Broadcast	YES (Max. 119 destinations)	YES (Max. 124 destinations)	YES (Max. 124 destinations) (MF6560PL)
Error Correction Mode (ECM)	YES	YES	YES (MF6560PL)
Memory Reception	YES	YES	YES (MF6560PL)
Polling	YES (Manual RX only)	YES (Manual RX only)	YES (Manual RX only) (MF6560PL)
SCANNER FUNCTIONS			
Scanner Type	Colour Flatbed	Colour Flatbed	Colour Flatbed
Scanner Resolution	1200 x 2400 dpi (9600 x 9600 dpi enhanced)	600 x 600 dpi (9600 x 9600 dpi enhanced)	600 x 600 dpi (9600 x 9600 dpi enhanced)
Colour Scanning Depth	48 bit/24 bit (in/out)	24 bit/24 bit (in/out)	24 bit/24 bit (in/out)
Greyscale Gradation	256 grey scale	256 grey scale	256 grey scale
Compatibility	TWAIN, WIA	TWAIN, WIA	TWAIN, WIA
OCR Bundle	YES	YES	YES
COPIER FUNCTIONS			
Copy Resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
Copy Modes	Text, Photo, Text and Photo	Text, Photo, Text and Photo	Text, Photo, Text and Photo
Copy Speed	19 copies per minute (mono), 4 copies per minute (colour)	22 copies per minute	22 copies per minute
Multiple Copy	Up to 99 copies	Up to 99 copies	Up to 99 copies
Zoom Ratio	50 – 200%	50 – 200%	50 – 200%
First Copy Output Time (FCOT)	Approx. 22 seconds	Approx. 8 seconds	Approx. 8 seconds
Other Features	Auto Exposure, Collate Copy, Reserve Copy	2-in-1 copy, Duplex copy	2-in-1 copy, Duplex copy
PC INTERFACE AND SOFTWARE			
Interface Type	USB 2.0 Hi-Speed, 10Base-T/100Base-TX	USB 2.0 Hi-Speed	USB 2.0 Hi-Speed
Supported OS	Windows® 98/ME/2000, Server 2003 (Network only), XP, Vista	Windows® 98/ME/2000/XP/Vista/Mac OS X Version 10.2.x, 10.3.x, 10.4.x, 10.5.x (English driver and online distribution only. No scanning)/Linux print drivers (English driver, online distribution only)	Windows® 98/ME/2000/XP/Vista/Mac OS X Version 10.2.x, 10.3.x, 10.4.x, 10.5.x (English driver and online distribution only. No scanning)/Linux print drivers (English driver, online distribution only)
Scan to E-mail	YES (Via PC)	YES (via PC)	YES (via PC)
Bundled Software	Presto!PageManager, ScanSoft OmniPage SE	Presto! PageManager, ScanSoft Omnipage SE	Presto! PageManager, ScanSoft Omnipage SE
NETWORK FEATURES			
Network Connectivity	YES - (built-in) (Print, PC Fax)	YES (built-in) (Network: Print and PC Fax only)	YES (Optional: AXIS Network Print Server)
Type	Ethernet (10Base-T/100Base-TX)	Ethernet (10Base-T/100Base-T)	Ethernet (10Base-T/100Base-T)
Network Protocols	TCP/IP	TCP/IP	TCP/IP
GENERAL SPECIFICATIONS			
Number of Language (LCD message)	15 languages	24 languages	24 languages
Dimensions without Trays (W x D x H)	510 x 512 x 588mm	520 x 420 x 451.9mm	520 x 420 x 451.9mm
Dimensions with Trays (W x D x H)	510 x 512 x 641mm	520 x 420 x 451.9mm	520 x 420 x 451.9mm
Weight	Approx. 36kg	23.7kg	23.7kg
Power Source	200-240V AC, 50-60Hz	200 – 240V AC, 50 – 60Hz	200 – 240V AC, 50 – 60Hz
Power Consumption	Max: Approx. 1200W, Standby: Approx. 35W, Sleep: 8W	Max: Approx. 860W, Standby: Approx. 20W, Sleep: 5W	Max: Approx. 860W, Standby: Approx. 20W, Sleep: 5W
Acoustic Noise Levels	Standby: under 35dB(A) max. During operation: under 54dB(A) max.	Standby: under 43dB(A) During operation: under 66dB(A)	Standby: under 43dB(A) During operation: under 66dB(A)

Standard disclaimer

[a] All specifications subject to change without notice

Footnotes

[1] Specification not available at time of print

Laser All-In-Ones Specifications

	i-SENSYS MF6550/MF6530	i-SENSYS MF4690PL	i-SENSYS MF4660PL
TYPE			
Machine Type	Laser Flatbed All-in-One	Laser Flatbed All-in-One	Laser Flatbed All-in-One
Available Functions	Fax (MF6550 only), Print, Copy, Colour Scan	Print, Fax, Copy, Colour Scan	Print, Copy, Colour Scan
Paper Scanning Type	Flatbed and Automatic Document Feeder	Flatbed and Automatic Document Feeder	Flatbed and Automatic Document Feeder
PRINTER FUNCTIONS			
Printing Method	Monochrome Laser beam printing	Monochrome Laser beam printing	Monochrome Laser beam printing
Printer Language	PCL6, Canon UFR-II LT	PCL5e/6 and Canon UFRII LT	PCL5e/6 and Canon UFRII LT
Print Speed	22 ppm	20 ppm	20 ppm
Duty Cycle	Up to 15,000 pages per month	10,000 pages per month	10,000 pages per month
Print Resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
Printer Memory	128MB Shared; 64MB Shared	128MB (shared)	128MB (shared)
Cartridges	Cartridge 706	FX-10 Cartridge	FX-10 Cartridge
Yield	5,000 pages (based on ISO/IEC19752)	2,000 pages (based on 5% coverage A4)	2,000 pages (based on 5% coverage A4)
Smoothing	1200 x 600 dpi	1200 x 600 dpi	1200 x 600 dpi
Paper Capacity	500 sheet cassette + 100 sheets Multipurpose tray (+500 sheet optional cassette)	250 sheet cassette + 1 sheet Multipurpose tray	250 sheet cassette + 1 sheet manual Multipurpose tray
Paper Size	A4, A5, B5, LTR, LGL, EXE, ENVELOPE, Index Cards	LTR, LGL, A4, B5, A5, Executive, Envelope (COM10, Monarch, DL, ISO-C5)	LTR, LGL, A4, B5, A5, Executive, Envelope (COM10, Monarch, DL, ISO-C5)
Printing Width	216mm	216mm	216mm
Duplex Print	Automatic (Standard)	Automatic (Standard)	Automatic (Standard)
Toner Saver Mode	YES	YES	YES
FAX FUNCTIONS			
Stand-alone Fax	YES (MF6550)	YES	NO
PC Fax	YES (TX only) (MF6550)	YES	—
Transmission Speed	Approx. 3 seconds per page (based on ITU-T Chart No.1) (MF6550)	Approx. 3 seconds per page (based on ITU-T Chart No.1)	—
Modem Speed	Super G3, 33.6Kbps (MF6550)	Super G3, 33.6Kbps	—
Compression Method	MH, MR, MMR, JBIG (MF6550)	MH, MR, MMR, JBIG	—
Fax Resolution	Standard, Fine, Super Fine, Ultra Fine (MF6550)	Standard, Fine, Photo, Super Fine, Ultra Fine	—
Image Processing System	UHQ (MF6550)	UHQ	—
Half-tone	256 grey scale (MF6550)	256 grey scale	—
Automatic Document Feeder	50 pages (Duplex) (MF6550)	35 pages	—
Memory Transmission	YES (MF6550)	YES	—
Fax Memory	256 pages (MF6550)	512 pages	—
Memory Back-up	YES (1 hour) (MF6550)	YES (Duration - 1 hour)	—
Dual Access	YES (MF6550)	YES	—
One-touch Dials/Coded Dials	23/100 (MF6550)	7/192	—/—
Group Dial	122 (MF6550)	198	—
Redial	YES (MF6550)	YES (automatic and manual)	—
Answering Machine Hook-up	YES (MF6550)	YES	—
Remote Reception	YES (MF6550)	YES	—
Sequential Broadcast	YES (max. 124 destinations) (MF6550)	YES (Max. 201 locations)	—
Error Correction Mode (ECM)	YES (MF6550)	YES	—
Memory Reception	YES (MF6550)	YES (512 pages)	—
Polling	YES (Manual RX only) (MF6550)	NO	—
SCANNER FUNCTIONS			
Scanner Type	Colour Flatbed	Colour Flatbed	Colour Flatbed
Scanner Resolution	600 x 600 dpi (9600 x 9600 dpi enhanced)	600 x 1200 dpi (9600 x 9600 dpi enhanced)	600 x 1200 dpi (9600 x 9600 dpi enhanced)
Colour Scanning Depth	24 bit/24 bit (in/out)	24 bit/24 bit (in/out)	24 bit/24 bit (in/out)
Greyscale Gradation	256 grey scale	256 grey scale	256 grey scale
Compatibility	TWAIN, WIA	TWAIN, WIA	TWAIN, WIA
OCR Bundle	YES	YES	YES
COPIER FUNCTIONS			
Copy Resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
Copy Modes	Text, Photo, Text and Photo	Text/Photo, Text/Photo+, Text and Photo	Text/Photo, Text/Photo+, Text and Photo
Copy Speed	22 copies per minute	20 copies per minute	20 copies per minute
Multiple Copy	Up to 99 copies	Up to 99 copies	Up to 99 copies
Zoom Ratio	50 - 200%	50% - 200%	50% - 200%
First Copy Output Time (FCOT)	Approx. 8 seconds	8.5 seconds	8.5 seconds
Other Features	2-in-1 copy, Duplex copy	2-in-1 copy, memory sort, Reduction, Enlargement, Duplex (only 1 to 2 sided), Secure Department ID	2-in-1 copy, memory sort, Reduction, Enlargement, Duplex (only 1 to 2 sided), Secure Department ID
PC INTERFACE AND SOFTWARE			
Interface Type	USB 2.0 Hi-Speed	USB 2.0 Hi-Speed	USB 2.0 Hi-Speed
Supported OS	Windows® 98/ME/2000/XP/Vista/Mac OS X Version 10.2.x, 10.3.x, 10.4.x, 10.5.x (English driver and online distribution only. No scanning)/Linux print drivers (English driver, online distribution only)	Windows® 98/ME/2000/Server 2003/XP/Vista/Mac OS X Version 10.2.x, 10.3.x, 10.4.x, 10.5.x (English driver and online distribution only. No scanning)/Linux print drivers (English driver, online distribution only)	Windows® 98/ME/2000/Server 2003/XP/Vista/Mac OS X Version 10.2.x, 10.3.x, 10.4.x, 10.5.x (English driver and online distribution only. No scanning)/Linux print driver (English driver, online distribution only)
Scan to E-mail	YES (via PC)	YES (via PC)	YES (via PC)
Bundled Software	Presto!PageManager, ScanSoft OmniPage SE	Presto!PageManager, ScanSoft OmniPage SE	Presto!PageManager, ScanSoft OmniPage SE
NETWORK FEATURES			
Network Connectivity	YES (with optional: AXIS Network Print Server)	YES (built-in) (Print, PC fax, Scan to Network (SMB), E-mail (SMB), E-mail, FAX, USB memory key)	YES (built-in) (Print)
Type	Ethernet (10Base-T/100Base-T)	Ethernet (100Base-T/1000Base-T)	Ethernet (100Base-T/1000Base-T)
Network Protocols	TCP/IP	TCP/IP	TCP/IP
Others	—	—	—
GENERAL SPECIFICATIONS			
Number of Language (LCD message)	24 languages	17 languages	17 languages
Dimensions without Trays (W x D x H)	520 x 420 x 451.9mm	390 x 442 x 370mm	390 x 442 x 370mm
Dimensions with Trays (W x D x H)	520 x 420 x 451.9mm	390 x 532 x 470mm	390 x 532 x 470mm
Weight	Approx. 23.7kg	Approx. 13.4kg	Approx. 13.4kg
Power Source	200 - 240V AC, 50 - 60Hz	200 - 240V AC, 50 - 60Hz	200 - 240V AC, 50 - 60Hz
Power Consumption	Max: Approx. 860W, Standby: Approx. 20W, Sleep: 5W	Max.: 730W, Standby: less than 12W, Sleep: Approx. 3W	Max.: 730W, Standby: less than 12W, Sleep: Approx. 3W
Acoustic Noise Levels	Standby: under 43dB(A) During operation: under 66dB(A)	Background noise level (during standby) max. 66dB or less (during printing or copying)	Background noise level (during standby) max. 66dB or less (during printing or copying)

Standard disclaimer

[2] All specifications subject to change without notice

Footnotes

[1] Specification not available at time of print

Laser All-In-Ones Specifications

	i-SENSYS MF4270	i-SENSYS MF4150	i-SENSYS MF4140
TYPE			
Machine Type	Laser Flatbed All-in-One	Laser Flatbed All-in-One	Laser Flatbed All-in-One
Available Functions	Print, Fax, Copy, Colour Scan	Print, Copy, Colour Scan, Fax	Print, Copy, Colour Scan, Fax
Paper Scanning Type	Flatbed and Automatic Document Feeder	Flatbed and Automatic Document Feeder	Flatbed
PRINTER FUNCTIONS			
Printing Method	Monochrome Laser beam printing	Monochrome Laser beam printing with built-in duplex unit	Monochrome Laser beam printing with built-in duplex unit
Printer Language	Canon UFRII LT	Canon UFRII LT	Canon UFRII LT
Print Speed	20 ppm	20 ppm	20 ppm
Duty Cycle	Up to 10,000 pages per month	Up to 10,000 pages per month	Up to 10,000 pages per month
Print Resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
Printer Memory	32MB (shared)	32MB (shared)	32MB (shared)
Cartridges	FX-10 Cartridge	FX-10 Cartridge	FX-10 Cartridge
Yield	2,000 pages (based on 5% coverage A4)	2,000 pages (based on 5% coverage A4)	2,000 pages (based on 5% coverage A4)
Smoothing	1200 x 600 dpi	1200 x 600 dpi	1200 x 600 dpi
Paper Capacity	250 sheet cassette + 1 sheet manual Multipurpose tray	250 sheet cassette + 1 sheet manual Multipurpose tray + 35 sheet Automatic Document Feeder	250 sheet cassette + 1 sheet manual Multipurpose tray
Paper Size	A4, A5, B5, LTR, LGL, EXE, ENVELOPE, Index Cards	LTR, LGL, A4, B5, A5, Executive, Envelope, Index Cards	A4, B5, LTR, LGL, EXE, ENVELOPE, Index Cards
Printing Width	216mm	216mm	216mm
Duplex Print	Automatic (Standard)	Automatic (Standard)	Automatic (Standard)
Toner Saver Mode	YES	YES	YES
FAX FUNCTIONS			
Stand-alone Fax	YES	YES	YES
PC Fax	YES	YES	YES
Transmission Speed	Approx. 3 seconds per page (based on ITU-T Chart No.1)	Approx. 3 seconds per page (based on ITU-T Chart No.1)	Approx. 3 seconds per page (based on ITU-T Chart No.1)
Modem Speed	Super G3, 33.6Kbps	Super G3, 33.6Kbps	Super G3, 33.6Kbps
Compression Method	MH, MR, MMR	MH, MR, MMR	MH, MR, MMR
Fax Resolution	Standard, Fine, Photo, Super Fine	Standard, Fine, Photo, Super Fine	Standard, Fine, Photo, Super Fine
Image Processing System	UHQ	UHQ	UHQ
Half-tone	256 grey scale	256 grey scale	256 grey scale
Automatic Document Feeder	35 pages	35 pages	NO
Memory Transmission	YES	YES	YES
Fax Memory	256 pages (4MB)	256 pages (4MB)	256 pages (4MB)
Memory Back-up	NO	NO	NO
Dual Access	YES	YES	YES
One-touch Dials/Coded Dials	7/100	7/100	7/100
Group Dial	7 (Max. 50 locations)	7 (Max. 50 locations)	7 (max. 50 locations)
Redial	YES (automatic and manual)	YES (automatic and manual)	YES (automatic and manual)
Answering Machine Hook-up	YES	YES	YES
Remote Reception	YES	YES	YES
Sequential Broadcast	YES (Max. 123 locations)	YES (Max. 123 locations)	YES (Max.123 locations)
Error Correction Mode (ECM)	YES	YES	YES
Memory Reception	YES (256 pages)	YES (256 pages)	YES (256 pages)
Polling	NO	NO	NO
SCANNER FUNCTIONS			
Scanner Type	Colour Flatbed	Colour Flatbed	Colour Flatbed
Scanner Resolution	600 x 1200 dpi (9600 x 9600 dpi enhanced)	600 x 1200 dpi (9600 x 9600 dpi enhanced)	600 x 1200 dpi (9600 x 9600 dpi enhanced)
Colour Scanning Depth	24 bit/24 bit (in/out)	24 bit/24 bit (in/out)	24 bit/24 bit (in/out)
Greyscale Gradation	256 grey scale	256 grey scale	256 grey scale
Compatibility	TWAIN, WIA	TWAIN, WIA	TWAIN, WIA
OCR Bundle	YES	YES	YES
COPIER FUNCTIONS			
Copy Resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
Copy Modes	Text/Photo, Text/Photo+, Text and Photo	Text/Photo, Text/Photo+, Text and Photo	Text/Photo, Text/Photo+, Text and Photo
Copy Speed	20 copies per minute	20 copies per minute	20 copies per minute
Multiple Copy	Up to 99 copies	Up to 99 copies	Up to 99 copies
Zoom Ratio	50% – 200%	50% – 200%	50% – 200%
First Copy Output Time (FCOT)	Less than 9 seconds	9.6 seconds	9.6 seconds
Other Features	2-in-1 copy, memory sort, Reduction, Enlargement, Duplex (only 1 to 2 sided)	2-in-1 copy, memory sort, Reduction, Enlargement, Duplex (only 1 to 2 sided)	2-in-1 copy, memory sort, Reduction, Enlargement, Duplex (only 1 to 2 sided)
PC INTERFACE AND SOFTWARE			
Interface Type	USB 2.0 Hi-Speed	USB 2.0 Hi-Speed	USB 2.0 Hi-Speed
Supported OS	Windows® 2000/Server 2003(Network only)/XP/Vista/ Mac OS X Version 10.2.x, 10.3.x, 10.4.x, 10.5.x (English driver and online distribution only. No scanning)	Windows® 98/ME/2000/XP/Vista/Mac OS X Version 10.2.x, 10.3.x, 10.4.x, 10.5.x (English driver and online distribution only. No scanning)/Linux print driver (English driver, online distribution only)	Windows® 98/ME/2000/XP/Vista/Mac OS X Version 10.2.x, 10.3.x, 10.4.x, 10.5.x (English driver and online distribution only. No scanning)/Linux print driver (English driver, online distribution only)
Scan to E-mail	YES (via PC)	YES (via PC)	YES (via PC)
Bundled Software	Presto!PageManager, ScanSoft OmniPage SE	Presto!PageManager, ScanSoft OmniPage SE	Presto!PageManager, ScanSoft OmniPage SE
NETWORK FEATURES			
Network Connectivity	YES (built-in) (Print, PC Fax)	YES (with optional Axis 1650 Network Print Server)	YES (with optional Axis 1650 Network Print Server)
Type	Ethernet (10Base-T/100Base-T)	Ethernet (10Base-T/100Base-T)	Ethernet (10Base-T/100Base-T)
Network Protocols	TCP/IP	TCP/IP	TCP/IP
GENERAL SPECIFICATIONS			
Number of Language (LCD message)	17 languages	17 languages	17 languages
Dimensions without Trays (W x D x H)	390 x 442 x 370mm	390 x 432 x 370mm	390 x 432 x 297mm
Dimensions with Trays (W x D x H)	390 x 532 x 455mm	390 x 532 x 455mm	390 x 532 x 297mm
Weight	Approx. 13.2kg	Approx. 12.4kg	Approx. 12.4kg
Power Source	200 – 240V AC, 50 – 60Hz	200 – 240V AC, 50 – 60Hz	200 – 240V AC, 50 – 60Hz
Power Consumption	Max.: 770W, Standby: less than 9W, Sleep: Approx. 3W	Max.: 650W, Standby: less than 8W, Sleep: Approx. 3.5W	Max.: 650W, Standby: less than 8W, Sleep: Approx. 3.5W
Acoustic Noise Levels	Background noise level only (during standby) 66dB or less (during printing or copying)	Standby: background noise, Copy: under 66dB(A) max.	Standby: background noise, Copy: under 66dB(A) max.

Standard disclaimer

[a] All specifications subject to change without notice

Footnotes

[1] Specification not available at time of print

Laser All-In-Ones Specifications

	i-SENSYS MF4120	i-SENSYS MF4010
TYPE		
Machine Type	Laser Flatbed All-in-One	Laser Flatbed All-in-One
Available Functions	Print, Copy, Colour Scan	Print, Copy, Colour Scan
Paper Scanning Type	Flatbed	Flatbed
PRINTER FUNCTIONS		
Printing Method	Monochrome Laser beam printing	Monochrome Laser beam printing
Printer Language	Canon UFRII LT	Canon UFRII LT
Print Speed	20 ppm	20 ppm
Duty Cycle	Up to 10,000 pages per month	Up to 10,000 pages per month
Print Resolution	600 x 600 dpi	600 x 600 dpi
Printer Memory	32MB (shared)	32MB (shared)
Cartridges	FX-10 Cartridge	FX-10 Cartridge
Yield	2,000 pages (based on 5% coverage A4)	2,000 pages (based on 5% coverage A4)
Smoothing	1200 x 600 dpi	1200 x 600 dpi
Paper Capacity	250 sheet cassette + 1 sheet Multipurpose tray	250 sheet cassette + 1 sheet Multipurpose tray
Paper Size	A4, A5, B5, LTR, LGL, EXE, ENVELOPE, Index Cards	A4, A5, B5, LTR, LGL, EXE, ENVELOPE, Index Cards
Printing Width	216mm	216mm
Duplex Print	Automatic (Standard)	No
Toner Saver Mode	YES	YES
FAX FUNCTIONS		
Stand-alone Fax	NO	NO
PC Fax	–	–
Transmission Speed	–	–
Modem Speed	–	–
Compression Method	–	–
Fax Resolution	–	–
Image Processing System	–	–
Half-tone	–	–
Automatic Document Feeder	–	–
Memory Transmission	–	–
Fax Memory	–	–
Memory Back-up	–	–
Dual Access	–	–
One-touch Dials/Coded Dials	–/–	–/–
Group Dial	–	–
Redial	–	–
Answering Machine Hook-up	–	–
Remote Reception	–	–
Sequential Broadcast	–	–
Error Correction Mode (ECM)	–	–
Memory Reception	–	–
Polling	–	–
SCANNER FUNCTIONS		
Scanner Type	Colour Flatbed	Colour Flatbed
Scanner Resolution	600 x 1200 dpi (9600 x 9600 dpi enhanced)	600 x 1200 dpi (9600 x 9600 dpi enhanced)
Colour Scanning Depth	24 bit/24 bit (in/out)	24 bit/24 bit (in/out)
Greyscale Gradation	256 grey scale	256 grey scale
Compatibility	TWAIN, WIA	TWAIN, WIA
OCR Bundle	YES	YES
COPIER FUNCTIONS		
Copy Resolution	600 x 600 dpi	300 x 300 dpi
Copy Modes	Text/Photo, Text/Photo+, Text and Photo	Text/Photo, Text/Photo+, Text and Photo
Copy Speed	20 copies per minute	20 copies per minute
Multiple Copy	Up to 99 copies	Up to 99 copies
Zoom Ratio	50% - 200%	50% - 200%
First Copy Output Time (FCOT)	9.6 seconds	less than 9 seconds
Other Features	2-in-1 copy, memory sort, Reduction, Enlargement, Duplex (only 1 to 2 sided)	Memory sort, Reduction, Enlargement
PC INTERFACE AND SOFTWARE		
Interface Type	USB 2.0 Hi-Speed	USB 2.0 Hi-Speed
Supported OS	Windows® 98/ME/2000/XP/Vista/Mac OS X Version 10.2.x, 10.3.x, 10.4.x, 10.5.x (English driver and online distribution only. No scanning)/Linux print driver (English driver, online distribution only)	Windows® 2000/XP/Vista/Mac OS X Version 10.2.x, 10.3.x, 10.4.x, 10.5.x (English driver and online distribution only. No scanning)/Linux print driver (English driver, online distribution only)
Scan to E-mail	YES (via PC)	YES (via PC)
Bundled Software	Presto!PageManager, ScanSoft OmniPage SE	Presto!PageManager, ScanSoft OmniPage SE
NETWORK FEATURES		
Network Connectivity	Optional Axis 1650 Network Print Server	Optional Axis 1650 Network Print Server
Type	Ethernet (10Base-T/100Base-T)	Ethernet (10Base-T/100Base-T)
Network Protocols	TCP/IP	TCP/IP
GENERAL SPECIFICATIONS		
Number of Language (LCD message)	17 languages	17 languages
Dimensions without Trays (W x D x H)	390 x 432 x 297mm	390 x 432 x 297mm
Dimensions with Trays (W x D x H)	390 x 532 x 297mm	390 x 532 x 297mm
Weight	Approx. 12.4kg	Approx. 12.7kg
Power Source	200 - 240V AC, 50 - 60Hz	200 - 240V AC, 50 - 60Hz
Power Consumption	Max.: 650W, Standby: less than 8W, Sleep: Approx. 3.5W	Max.: 650W, Standby: less than 8W, Energy Save Mode: Approx. 3.5W
Acoustic Noise Levels	Standby: background noise, Copy: under 66dB(A) max.	Standby: background noise Copy: under 66dB(A) max.

Standard disclaimer

[2] All specifications subject to change without notice

Footnotes

[1] Specification not available at time of print